

MOTORIZED SCENIC ROLLER SCREEN

Automatic Electric Projection Screen Model SPECIFICATION DATA

DA-LITE SCREEN COMPANY LLC

3100 North Detroit Street Post Office Box 137 Warsaw, Indiana 46581-0137 P 800-622-3737 / 574-267-8101 F 877-325-4832 / 574-267-7804 www.da-lite.com

e-mail: info@da-lite.com

SUGGESTED SPECIFICATIONS:	projection screen(s),	(H) x	(W), electrically
operated by two motors and 1/8" steel cable to r	aise and lower screen. Each moto	or to be 120 volt (60 Hz) n	ot more than 2.4 amp. Motors
to be three wire with ground quick reversal ty			
built in brake to prevent coasting. To have pre			
"down" positions. Motors to turn drum to allo	ow cable to roll bottom 5" diamet	er roller "up" and "down	" on fabric. Screen to have a
straight, rigid tubular metal header, 3" in diame	eter. Top of fabric shall be forme	d into a pocket into whic	h header shall be inserted. 3"
wide double "C" type clamps of high tensile st	trength cast aluminum shall be se	cured to header for hangi	ng. Furnished with a wing nut
for adjusting fabric hang. Fabric shall be flam	ne retardant and mildew resista	nt fiberglass with black r	masking borders standard on
fiberglass fabric. Fabric shall be securely faste	ened to roller. The header shall	be 2" longer than the wid	dth of the fabric. Ends of the
tubular header shall be protected with cast all	uminum end caps. The bottom r	oller, with the cable drum	ns, will be 12" wider than the
width of fabric. Bottom inner drum shall be see	cured inside the bottom roller. Bo	ttom outer drums shall be	e adjustable with one bolt and
two locking set screws. Bottom roller level can	be adjusted by rotating the outer	radjustable drums. Screer	n to be listed by Underwriters'
Laboratories.			

Matte White: See chart for seam locations.

High Power®: Seamless in sizes up to 8' high. Not available in sizes over 15' high.

DIMENSIONS

Dill'El TOTO								
Si	izes	Overall Length of Header		Overall Length Appro		Approx.	x. Ship. Wt.	Matte White
ΗxW	Cm	In.	Cm	ln.	Cm	Lbs.	Kg	Seam Location
10' 6" x 14'	320 x 427	170"	432	182"	462	680	308.4	Seamless
14' x 14'	427 x 427	170"	432	182"	462	689	312.5	Seamless
6' x 16'	183 x 488	194"	493	206"	523	725	328.9	Seamless
12' x 16'	366 x 488	194"	493	206"	523	741	336.1	Seamless
16' x 16'	488 x 488	194"	493	206"	523	751	340.6	Seamless
7' x 18'	213 x 549	218"	554	230"	584	791	358.8	Seamless
13' 6" x 18'	411 x 549	218"	554	230"	584	811	367.9	Seamless
18' x 18'	549 x 549	218"	554	230"	584	824	373.8	Horizontal Seam at 16'
15' x 20'	457 x 610	242"	615	254"	645	873	396.0	Seamless
20' x 20'	610 x 610	242"	615	254"	645	885	401.4	Horizontal Seam at 16'
18' x 24'	549 x 732	290"	737	302"	767	1011	458.6	Horizontal Seam at 16'
24' x 24'	732 x 732	290"	737	302"	767	1035	469.5	Horizontal Seam Every 8'
21' x 28'	640 x 853	338"	859	350"	889	1154	523.5	Horizontal Seam Every 8'
28' x 28'	853 x 853	338"	859	350"	889	1187	538.4	Horizontal Seam Every 8'
22' 6" x 30'	686 x 914	362"	920	374"	950	1222	554.3	Horizontal Seam Every 8'
30' x 30'	914 x 914	362"	920	374"	950	1259	571.1	Horizontal Seam Every 8'

PLEASE MARK APPROPRIATE SELECTIONS:

Select size from chart above.

Select viewing surface:

☐ Matte White ☐ ☐

and Schools Certified.

Optional Accessories:

- ☐ No borders (Black masking borders standard).
- ☐ Extra Drop available to lower picture area more than normal. Specify total drop at top _ (black or white) or at bottom _ (black or white). 30' maximum total surface height including picture area.
- Radio Frequency Wireless Remote Control. ☐ Radio Frequency Range Extender available

Project:	
Architect:	
Phone:	
Contractor:	
Phone:	
Supervisor:	
Phone:	
Date:	
Revised:	

Specifications subject to change without notice.

Detail dimensional drawings, wiring diagrams and installation instructions available upon request. Custom formats and sizes available upon request. Contact Da-Lite for seamless capability or seamed requirements for custom sizes.

