

## MATERIAL SAFETY DATA SHEET

Goo Systems Inc.  
4 Harvey Street  
Kingston, Ontario  
K7K 5B9

Phone (613) 541-0299

Fax (613) 541-1765

### SECTION # 1: PRODUCT IDENTIFICATION

**Product Identifier:** Screen Goo FINISH coats (except Ultra Silver 3D)  
**Whmis Classification:** Not Controlled.  
**MSDS Preparation Date:** 21 October 2010

### SECTION 2: HAZARDS IDENTIFICATION

#### Potential Acute Health

##### Inhalation

Pigment powders in this paint are not in the form of respirable dusts, hence they do not pose the hazards associated with the inhalation of fine mineral particles. Sanding of dried paint surfaces may result in these pigments becoming airborne and causing respiratory irritation. Under spray painting conditions, exposure may cause respiratory irritation.

##### Eye Contact

Prolonged or repeated contact may result in eye irritation.

##### Skin Contact

Prolonged or repeated contact may result in skin irritation.

##### Ingestion

May cause irritation to the gastrointestinal system.

#### Additional Exposure Information

Existing skin, eye, or respiratory conditions may be aggravated by exposure.

#### Potential Chronic Health Effects

Additional information see toxicological information (Section 11).

#### Medical Conditions Aggravated

### SECTION 3: COMPOSITIONS DATA

The Screen Goo topcoats contain ingredients found in the Whmis Ingredient Disclosure List:

| INGREDIENTS      | %Wt/Wt     | C.A.S.#    | TLV | LD50 (g/KG) |
|------------------|------------|------------|-----|-------------|
| Propylene Glycol | 1.0 - 12.5 | 57-55-56   | NA  | 20 (RAT)    |
| Texanol          | 1.0 - 2.0  | 25265-77-4 | NA  | < 3.2 (RAT) |

NOTES: NA = NOT AVAILABLE

### SECTION 4: FIRST AID PROCEDURES

**Eye Contact:** Flush with clean water for a minimum of 15 minutes. See a physician after flushing eyes.

**Skin Contact:** Wash hands with soap and water. If irritation develops see a physician.

**Inhalation:** Remove subject to fresh air.

**Ingestion:** May cause abdominal pain. Do not induce vomiting. Product is not considered toxic in small amounts. Call a physician. Ingestion of large amounts may require medical attention.

### SECTION 5: FIRE AND EXPLOSION HAZARD DATA

**Flammability Classification:** Not Applicable  
**Flash Point:** Not Combustible  
**Flammable Limits (% vol. in air):** LEL: N. App. UEL: N. App.  
**Extinguishing Media:** Not Applicable.

**Special Fire Fighting Procedures:** Material in paint can splatter above 100C. Dried paint film can burn. If this should occur use carbon dioxide, foam, dry chemical or water to extinguish. Wear full-body protective clothing and self-contained breathing apparatus. Do not direct extinguishing media directly into center of burning pools.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Spill/ Leak Procedure:** Contain spilled paint and clean up. Avoid excessive inhalation and skin contact.

## **SECTION 7: HANDLING AND STORAGE PRECAUTIONS**

**Storage of Paint:** Keep from freezing. Keep containers closed.  
Keep jar or cylinder tightly closed.

## **SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

### **General Protective and Hygiene Measures**

Do not eat, drink, smoke or sniff while working. Wash hands before breaks and at the end of work.

### **Respiratory Protection**

If spray painting or sanding, wear appropriate government approved mask. Ensure room has adequate ventilation.

### **Ventilation**

For professional (daily) use adequate ventilation is recommended, (i.e. window fan).

### **Eye Protection**

Wear safety glasses (with side shields) or goggles.

### **Skin Protection**

Gloves that do not absorb liquids( i.e. rubber or latex) are recommended.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **General Information**

|                      |  |
|----------------------|--|
| Form:                | Liquid                                       |
| Colour:              | White or Colored Liquid                      |
| Odour:               | Very Mild Ammonia Odour                      |
| Change in Condition  |  |
| Melting Point        | Undetermined                                 |
| Boiling Point        | 100 - 130 Deg. C                             |
| Flash Point          | Not Applicable                               |
| Auto Ignition        | Product is not self-igniting                 |
| Danger of Explosion  | Product does not present an explosion hazard |
| Specific Gravity:    | 1.0 - 1.7 (Water = 1.0)                      |
| Solubility in Water: | Dilutable                                    |

## **SECTION 10: STABILITY AND REACTIVITY DATA**

**Stability:** Stable

### **Incompatibility**

Maintain storage between 0 and 30 °C. Avoid strong oxidizing and reducing agents; strong acids and bases. Keep product away from open flame.

### **Conditions to Avoid**

Keep product from excessive heat.

### **Hazardous Decomposition Products**

Low molecular weight hydrocarbons, CO, CO<sub>2</sub>, NO<sub>x</sub>, trace HCl and H<sub>2</sub>S (with Ultramarine Blue). All are toxic.

## SECTION 11: TOXICOLOGICAL INFORMATION

The Screen Goo topcoats contain ingredients found in the Whmis Ingredient Disclosure List:

| <b>INGREDIENTS</b> | <b>%Wt/Wt</b> | <b>C.A.S.#</b> | <b>TLV</b> | <b>LD50 (g/KG)</b> |
|--------------------|---------------|----------------|------------|--------------------|
| Propylene Glycol   | 1.0 - 12.5    | 57-55-56       | NA         | 20 (RAT)           |
| Texanol            | 1.0 - 2.0     | 25265-77-4     | NA         | < 3.2 (RAT)        |

NOTES: NA = NOT AVAILABLE

### Chronic Effects on Humans

**Carcinogenic Effects**  
**Mutagenic Effects**  
**Teratogenic Effects**  
**Developmental Toxicity**

**California Proposition 65** No Statement required

Conforms to ASTM D-4236

**Acute Effects on Humans** May cause skin, eye and respiratory irritation.

## SECTION 12: ECOLOGICAL INFORMATION

General Notes

Information regarding the ecological impact of this product is not known at this time.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Paint Disposal:** Dispose of paint soaked rags and empty containers in accordance with local regulations.

## SECTION 14: TRANSPORT INFORMATION

DOT Regulations Hazard Class - No Hazard Class  
NMFC classification: 55  
Acrylic Paint Non-Hazardous NMFC number: 149980-2  
Heated transport is not required

IATA SHIPPING NAME: (PAINT RELATED MATERIAL)  
IATA HAZARD CLASS: (NON-HAZARDOUS)  
Land Transport TDG TDG Class - No TDG Class

## SECTION 15: Regulations

**WHMIS** Not Controlled.

**Proposition 65** No Statement required

**SCAQMD** Classified as "Other"

## SECTION 16: OTHER INFORMATION

While Goo Systems Inc. has prepared this MSDS from a knowledge of the products' components and from supplier information, there is no warranty with respect to the accuracy of this data. We assume no legal responsibility. All data is offered for your consideration, investigation and verification.